### **Chapter 3 - Decisions**



#### **Chapter Goals**



- •To implement decisions using the if statement
- •To compare integers, floating-point numbers, and Strings
- •To write statements using the Boolean data type
- •To develop strategies for testing your programs
- To for validate user input

## The **if** Statement

- A computer program often needs to make decisions based on input, or circumstances
- For example, buildings often 'skip' the 13<sup>th</sup> floor, and elevators should too
  - The 14<sup>th</sup> floor is really the 13<sup>th</sup> floor
  - So every floor above 12 is really 'floor 1'
    - If floor > 12, Actual floor = floor 1
- The two keywords of the if statement are:
  - if
  - else



• The *if* statement allows a program to carry out different actions depending on the nature of the data to be processed.

### Flowchart of the **if** Statement



## Flowchart with only a True Branch

#### •An if statement may not need a 'False' (else) branch



#### Syntax 3.1 The if Statement



## ElevatorSimulation.java

```
import java.util.Scanner;
 1
 2
 3
    /**
       This program simulates an elevator panel that skips the 13th floor.
 4
 5
    */
 6
    public class ElevatorSimulation
 7
 8
       public static void main(String[] args)
 9
        £
10
          Scanner in = new Scanner(System.in);
11
          System.out.print("Floor: ");
12
          int floor = in.nextInt();
13
          // Adjust floor if necessary
14
15
16
          int actualFloor;
17
          if (floor > 13)
18
          {
19
              actualFloor = floor - 1;
                                             Program Run
20
           }
21
                                               Floor: 20
          else
22
           {
                                               The elevator will travel to the actual floor 19
23
              actualFloor = floor;
24
          }
25
26
          System.out.println("The elevator will travel to the actual floor "
27
              + actualFloor);
28
       }
29
```

In some Asian countries, the number 14 is considered unlucky. Some building owners play it safe and *skip* both the thirteenth and the fourteenth floor. How would you modify the sample program to handle such a building?

```
Answer: Change the if statement to
```

```
if (floor > 14)
{
    actualFloor = floor - 2;
}
```

Consider the following if statement to compute a discounted price:

```
if (originalPrice > 100)
{
    discountedPrice = originalPrice - 20;
}
else
{
    discountedPrice = originalPrice - 10;
}
What is the discounted price if the original price is 95? 100? 105?
```

Answer: 85. 90. 85.

Compare this if statement with the one in Self Check 2:

```
if (originalPrice < 100)
{
    discountedPrice = originalPrice - 10;
}
else
{
    discountedPrice = originalPrice - 20;
}</pre>
```

Do the two statements always compute the same value? If not, when do the values differ?

**Answer:** The only difference is if originalPrice is 100. The statement in Self Check 2 sets discountedPrice to 90; this one sets it to 80.

Consider the following statements to compute a discounted price:

```
discountedPrice = originalPrice;
if (originalPrice > 100)
{
    discountedPrice = originalPrice - 10;
}
```

What is the discounted price if the original price is 95? 100? 105?

**Answer:** 95. 100. 95.

The variables fuelAmount and fuelCapacity hold the actual amount of fuel and the size of the fuel tank of a vehicle. If less than 10 percent is remaining in the tank, a status light should show a red color; otherwise it shows a green color. Simulate this process by printing out either "red" or "green".

#### Answer:

```
if (fuelAmount < 0.10 * fuelCapacity)
{
    System.out.println("red");
}
else
{
    System.out.println("green");
}</pre>
```

## **Tips On Using Braces**

Always use braces

Although single statement clauses do not require them

```
if (floor > 13) if (floor > 13)
{
    floor--;
}
```

•Most programmer's editors have a tool to align matching braces.

# **Tips on Indenting Blocks**

```
•Use Tab to indent a consistent number of spaces
```

```
public class ElevatorSimulation
   public static void main(String[] args)
      int floor;
      if (floor > 13)
         floor--;
             Indentation level
         3
```



•This is referred to as 'block- structured' code. Indenting consistently makes code much easier for humans to follow.

# **Common Error**



•The 'body' (between the curly braces) will always be executed in this case

### The Conditional Operator

A 'shortcut' you may find in existing code

 It is not used in this book
 Condition
 True branch
 False branch

 actualFloor = floor > 13 ? floor - 1 : floor;

Includes all parts of an if-else clause, but uses:

- •? To begin the true branch
- •: To end the true branch and start the false branch

## **Comparing Numbers and Strings**

Every if statement has a condition

Usually compares two values with an operator

	Table 1 Relational Operators		
<pre>if (floor &gt; 13)  if (floor &gt;= 13)  if (floor &lt; 13)  if (floor &lt;= 13)  </pre>	Java	Math Notation	Description
	>	>	Greater than
	>=	2	Greater than or equal
	<	<	Less than
if (floor == 13)	<=	$\leq$	Less than or equal
Beware		=	Equal
	!=	≠	Not equal

#### Syntax 3.2 Comparisons



## **Operator Precedence**

•The comparison operators have lower precedence than arithmetic operators

- •Calculations are done before the comparison
- •Normally your calculations are on the 'right side' of the comparison or assignment operator



## **Relational Operator Use**

Table 2 Relational Operator Examples				
Expression	Value	Comment		
3 <= 4	true	3 is less than 4; <= tests for "less than or equal".		
<b>○</b> 3 =< 4	Error	The "less than or equal" operator is <=, not =<. The "less than" symbol comes first.		
3 > 4	false	> is the opposite of <=.		
4 < 4	false	The left-hand side must be strictly smaller than the right-hand side.		
4 <= 4	true	Both sides are equal; <= tests for "less than or equal".		
3 == 5 - 2	true	== tests for equality.		
3 != 5 - 1	true	!= tests for inequality. It is true that 3 is not $5 - 1$ .		
S 3 = 6 / 2	Error	Use == to test for equality.		
1.0 / 3.0 == 0.333333333	false	Although the values are very close to one another, they are not exactly equal. See Common Error 3.2 on page 93.		
<b>\( 10" &gt; 5</b>	Error	You cannot compare a string to a number.		
"Tomato".substring(0, 3).equals("Tom")	true	Always use the equals method to check whether two strings have the same contents.		
"Tomato".substring(0, 3) == ("Tom")	false	Never use == to compare strings; it only checks whether the strings are stored in the same location. See Common Error 3.3 on page 94.		

## **Comparing Strings**

- •Strings are a bit 'special' in Java
- •Do not use the == operator with Strings
  - •The following compares the locations of two strings, and not their contents

```
if (string1 == string2) ...
```

Instead use the String's equals method:

```
if (string1.equals(string2)) ...
```

Which of the following conditions are true, provided  ${\rm a}$  is 3 and  ${\rm b}$  is 4?

a. a + 1 <= b</li>
b. a + 1 >= b
c. a + 1 != b

**Answer:** (a) and (b) are both true, (c) is false.

#### Give the opposite of the condition

floor > 13

**Answer:** floor <= 13

#### What is the error in this statement?

```
if (scoreA = scoreB)
{
   System.out.println("Tie");
}
```

**Answer:** The values should be compared with ==, not =.

Supply a condition in this if statement to test whether the user entered a Y:

```
System.out.println("Enter Y to quit.");
String input = in.next();
if (. . .)
{
    System.out.println("Goodbye.");
}
```

Answer: input.equals("Y")

How do you test that a string str is the empty string?

```
Answer: str.equals("") Or str.length() == 0
```

## **Common Error**

```
    Comparison of Floating-Point Numbers
```

- •Floating-point numbers have limited precision
- Round-off errors can lead to unexpected results

```
double r = Math.sqrt(2.0);
if (r * r == 2.0)
{
   System.out.println("Math.sqrt(2.0) squared is 2.0");
}
else
{
   System.out.println("Math.sqrt(2.0) squared is not 2.0
    but " + r * r);
}
  Output:
  Math.sqrt(2.0) squared is not 2.0 but 2.00000000000000044
```

## The Use of EPSILON

- •Use a very small value to compare the difference if floating-point values are '*close enough*'
  - •The magnitude of their difference should be less than some threshold
  - •Mathematically, we would write that x and y are close enough if:

$$|x-y|<\varepsilon$$

```
final double EPSILON = 1E-14;
double r = Math.sqrt(2.0);
if (Math.abs(r * r - 2.0) < EPSILON)
{
    System.out.println("Math.sqrt(2.0) squared is approx.
        2.0");
}
```

## **Common Error**

```
Using == to compare Strings
```

e== compares the locations of the Strings

 Java creates a new String every time a new word inside double-quotes is used

If there is one that matches it exactly, Java re-uses it

```
String nickname = "Rob";
...
if (nickname == "Rob") // Test is true
```

```
String name = "Robert";
String nickname = name.substring(0, 3);
...
if (nickname == "Rob") // Test is false
```

## Lexicographical Order

•To compare Strings in 'dictionary' order

•When compared using compareTo, string1 comes:

•Before string2 if	<pre>string1.compareTo(string2) &lt; 0</pre>
•After string2 if	<pre>string1.compareTo(string2) &gt; 0</pre>
•Equal to string2 if	<pre>string1.compareTo(string2) == 0</pre>

Notes

- All UPPERCASE letters come before lowercase
- •'space' comes before all other printable characters
- Digits (0-9) come before all letters
- -See Appendix A for the Basic Latin Unicode (ASCII) table

## Implementing an if Statement

- 1) Decide on a branching condition
- 2) Write pseudocode for the true branch
- 3) Write pseudocode for the false branch
- 4) Double-check relational operators

Test values below, at, and above the comparison (127, 128, 129)

- 5) Remove duplication
- 6) Test both branches
- 7) Write the code in Java

original price < 128? discounted price = 0.92 x original price discounted price = 0.84 x original price

discounted price = \_\_\_\_ x original price discounted price = 0.92 x 100 = 92 discounted price = 0.84 x 200 = 168

## Implemented Example

•The university bookstore has a Kilobyte Day sale every October 24, giving an 8 percent discount on all computer accessory purchases if the price is less than \$128, and a 16 percent discount if the price is at least \$128.

```
if (originalPrice < 128)
{
    discountRate = 0.92;
}
else
{
    discountRate = 0.84;
}
discountedPrice = discountRate * originalPrice;</pre>
```

## **Multiple Alternatives**

•What if you have more than two branches?

•Count the branches for the following earthquake effect example:

	Table 3 Richter Scale		
<ul> <li>8.0 (or greater)</li> <li>&gt;= 7.0 but &lt; 8.0</li> <li>&gt;= 6.0 but &lt; 7.0</li> <li>&gt;= 4.5 but &lt; 6.00</li> <li>Less than 4.5</li> </ul>	Value	Effect	
	8	Most structures fall	
	7	Many buildings destroyed	
	6	Many buildings considerably damaged, some collapse	
	4.5	Damage to poorly constructed buildings	

•When using multiple if statements, test general conditions after more specific conditions.

### Flowchart of Multiway Branching



## if, else if Multiway Branching

```
if (richter >= 8.0) // Handle the 'special case' first
 System.out.println("Most structures fall");
else if (richter >= 7.0)
 System.out.println("Many buildings destroyed");
else if (richter >= 6.0)
 System.out.println("Many buildings damaged, some
collapse");
else if (richter >= 4.5)
 System.out.println("Damage to poorly constructed
buildings");
else // so that the 'general case' can be handled last
 System.out.println("No destruction of buildings");
```

#### What Is Wrong with this Code?

```
if (richter \geq 8.0)
 System.out.println("Most structures fall");
if (richter \geq 7.0)
 System.out.println("Many buildings destroyed");
if (richter \geq 6.0)
 System.out.println("Many buildings damaged, some collapse");
if (richter \geq 4.5)
 System.out.println("Damage to poorly constructed buildings");
```
In a game program, the scores of players A and B are stored in variables <code>scoreA</code> and <code>scoreB</code>. Assuming that the player with the larger score wins, write an <code>if/else</code> if/else sequence that prints out "A won", "B won", or "Game tied".

#### Answer:

```
if (scoreA > scoreB)
   System.out.println("A won");
}
else if (scoreA < scoreB)</pre>
{
   System.out.println("B won");
else
   System.out.println("Game tied");
}
```

Write a conditional statement with three branches that sets s to 1 if x is positive, to -1 if x is negative, and to 0 if x is zero.

#### Answer:

if (x > 0) { s = 1; }
else if (x < 0) { s = -1; }
else { s = 0; }</pre>

How could you achieve the task of Self Check 12 with only two branches?

**Answer:** You could first set s to one of the three values:

s = 0; if (x > 0) { s = 1; } else if (x < 0) { s = -1; }</pre>

Beginners sometimes write statements such as the following:

```
if (price > 100)
{
    discountedPrice = price - 20;
}
else if (price <= 100)
{
    discountedPrice = price - 10;
}</pre>
```

Explain how this code can be improved.

**Answer:** The if (price <= 100) can be omitted (leaving just else), making it clear that the else branch is the sole alternative.

Suppose the user enters -1 into the earthquake program. What is printed?

**Answer:** No destruction of buildings.

Suppose we want to have the earthquake program check whether the user entered a negative number. What branch would you add to the if statement, and where?

**Answer:** Add a branch before the final else:

```
else if (richter < 0)
{
   System.out.println("Error: Negative input");
}</pre>
```

### Another Way to Multiway Branch

•The switch statement chooses a case based on an integer value.

•break ends each case

•default catches all other values

•If the break is missing, the case falls through to the next case's statements.

```
int digit = . . .;
switch (digit)
{
  case 1: digitName = "one"; break;
  case 2: digitName = "two"; break;
  case 3: digitName = "three"; break;
  case 4: digitName = "four"; break;
  case 5: digitName = "five"; break;
  case 6: digitName = "six"; break;
  case 7: digitName = "seven"; break;
  case 8: digitName = "eight"; break;
  case 9: digitName = "nine"; break;
  default: digitName = ""; break;
```

#### **Nested Branches**

•You can *nest* an *if* inside either branch of an *if* statement.

•Simple example: Ordering drinks

•Ask the customer for their drink order

•if customer orders wine

Ask customer for ID

•if customer's age is 21 or over

Serve wine

Else

Politely explain the law to the customer

Else

•Serve customers a non-alcoholic drink

#### Flowchart of a Nested if

•Nested if-else inside true branch of an if statement.

Three paths



## Tax Example: Nested ifs

#### •Four outcomes (branches)

■Single ■<= 32000	If your status is Single and if the taxable income is	the tax is	of the amount over
•> 32000	at most \$32,000	10%	\$0
<ul> <li>Married</li> </ul>	over \$32,000	\$3,200 + 25%	\$32,000
■ <= 64000 ■> 64000	If your status is Married and if the taxable income is	the tax is	of the amount over
	at most \$64,000	10%	\$0
	over \$64,000	\$6,400 + 25%	\$64,000

Table 4 Federal Tax Rate Schedule

#### Flowchart for Tax Example



# TaxCalculator.java (1)

```
import java.util.Scanner;
 2
 3
    /**
 4
       This program computes income taxes, using a simplified tax schedule.
 5
    */
    public class TaxCalculator
 6
 7
 8
       public static void main(String[] args)
 9
        5
10
          final double RATE1 = 0.10:
11
          final double RATE2 = 0.25;
12
          final double RATE1 SINGLE LIMIT = 32000;
13
          final double RATE1 MARRIED LIMIT = 64000;
14
15
          double tax1 = 0;
16
          double tax2 = 0:
17
          // Read income and marital status
18
19
20
          Scanner in = new Scanner(System.in);
21
          System.out.print("Please enter your income: ");
22
          double income = in.nextDouble();
23
24
          System.out.print("Please enter s for single, m for married: ");
25
          String maritalStatus = in.next();
26
```

## TaxCalculator.java (2)

•The 'True' branch (Married)

•Two branches within this branch

```
// Compute taxes due
27
28
29
           if (maritalStatus.equals("s"))
30
           {
31
              if (income <= RATE1_SINGLE LIMIT)</pre>
32
              ł
33
                 tax1 = RATE1 * income;
34
              }
35
              else
36
              £
37
                 tax1 = RATE1 * RATE1_SINGLE_LIMIT;
38
                 tax2 = RATE2 * (income - RATE1 SINGLE LIMIT);
39
              }
40
           }
```

## TaxCalculator.java (3)

•The 'False' branch (Not married)

```
41
           else
42
           {
43
              if (income <= RATE1 MARRIED LIMIT)
44
               {
                                                     Program Run
45
                 tax1 = RATE1 * income;
                                                       Please enter your income: 80000
46
               }
                                                       Please enter s for single, m for married: m
47
              else
                                                       The tax is $10400
48
               {
49
                  tax1 = RATE1 * RATE1 MARRIED LIMIT;
50
                  tax2 = RATE2 * (income - RATE1 MARRIED LIMIT);
51
               }
52
           }
53
54
           double totalTax = tax1 + tax2;
55
56
           System.out.println("The tax is $" + totalTax);
57
        }
58
     }
```

What is the amount of tax that a single taxpayer pays on an income of \$32,000?

**Answer:** 3200.

Would that amount change if the first nested if statement changed from
if (income <= RATE1\_SINGLE\_LIMIT)
to</pre>

```
if (income < RATE1_SINGLE_LIMIT)</pre>
```

```
Answer: No. Then the computation is 0.10 × 32000 + 0.25 × (32000 – 32000).
```

Suppose Harry and Sally each make \$40,000 per year. Would they save taxes if they married?

**Answer:** No. Their individual tax is \$5,200 each, and if they married, they would pay \$10,400. Actually, taxpayers in higher tax brackets (which our program does not model) may pay higher taxes when they marry, a phenomenon known as the *marriage penalty*.

How would you modify the TaxCalculator.java program in order to check that the user entered a correct value for the marital status (i.e., s or m)?

```
Answer: Change else in line 41 to
```

```
else if (maritalStatus.equals("m"))
```

and add another branch after line 52:

```
else
{
   System.out.println(
    "Error: marital status should be s or m.");
}
```

Some people object to higher tax rates for higher incomes, claiming that you might end up with less money after taxes when you get a raise for working hard. What is the flaw in this argument?

**Answer:** The higher tax rate is only applied on the income in the higher bracket. Suppose you are single and make \$31,900. Should you try to get a \$200 raise? Absolutely: you get to keep 90 percent of the first \$100 and 75 percent of the next \$100.

# Hand-Tracing

-Hand-tracing helps you understand whether a program works correctly

- Create a table of key variables
  - •Use pencil and paper to track their values
- Works with pseudocode or code
- Track location with a marker such as a paper clipUse example input values that:
  - •You know what the correct outcome should be
  - •Will test each branch of your code



# Hand-Tracing Tax Example (1)

Setup

- Table of variables
- Initial values

tax2	income	marital status
0		
	tax2 0	tax2 income 0

```
public static void main(String[] args)
8
9
   {
10
      final double RATE1 = 0.10;
11
      final double RATE2 = 0.25;
      final double RATE1_SINGLE_LIMIT = 32000;
12
      final double RATE1_MARRIED_LIMIT = 64000;
13
14
      double tax1 = 0;
15
      double tax2 = 0;
16
17
```

# Hand-Tracing Tax Example (2)

Input	variables
-------	-----------

From user

•Update table

tax 1	tax2	income	marital status
0	0	80000	m

```
20 Scanner in = new Scanner(System.in);
21 System.out.print("Please enter your income: ");
22 double income = in.nextDouble();
23
24 System.out.print("Please enter s for single, m for married: ");
25 String maritalStatus = in.next();
```

Because marital status is not "s" we skip to the else on line 41

## Hand-Tracing Tax Example (3)

Because income is not <= 64000, we move to the else clause on line 47

- •Update variables on lines 49 and 50
- Use constants

```
marital
                                              tax1
                                                        tax2
                                                                  income
                                                                             status
                                                ø
                                                          Ø
                                                                  80000
                                                                               M
                                              6400
                                                        4000
         if (income <= RATE1_MARRIED_LIMIT)
43
44
         {
45
            tax1 = RATE1 * income;
46
         }
47
         else
48
         {
            tax1 = RATE1 * RATE1_MARRIED_LIMIT;
49
50
            tax2 = RATE2 * (income - RATE1_MARRIED_LIMIT);
51
         }
```

# Hand-Tracing Tax Example (4)

#### Output

- -Calculate
- As expected?

tax 1	tax2	income	marital status	total tax
,Ø	Ø	80000	m	
6400	4000			10400

```
54 double totalTax = tax1 + tax2;
55
```

```
56 System.out.println("The tax is $" + totalTax);
```

57 }

## **Common Error**

#### •The Dangling else Problem

•When an  $\mathtt{if}$  statement is nested inside another  $\mathtt{if}$  statement, the following can occur:

```
double shippingCharge = 5.00; // $5 inside continental U.S.
if (country.equals("USA"))
    if (state.equals("HI"))
        shippingCharge = 10.00; // Hawaii is more expensive
else // Pitfall!
    shippingCharge = 20.00; // As are foreign shipment
```

-The indentation level suggests that the <code>else</code> is related to the <code>if</code> country ("USA")

•Else clauses always associate to the closest if

## **Enumerated Types**

Java provides an easy way to name a finite list of values that a variable can hold
It is like declaring a new type, with a list of possible values

```
public enum FilingStatus {
   SINGLE, MARRIED, MARRIED FILING SEPARATELY }
```

- •You can have any number of values, but you must include them all in the enum declaration
- •You can declare variables of the enumeration type:

```
FilingStatus status = FilingStatus.SINGLE;
```

And you can use the comparison operator with them:

```
if (status == FilingStatus.SINGLE) . . .
```

## **Problem Solving: Flowcharts**

- •You have seen a few basic flowcharts
- A flowchart shows the structure of decisions and tasks to solve a problem
- -Basic flowchart elements:



inside another branch!

# **Conditional Flowcharts**



## Shipping Cost Flowchart

Shipping costs are \$5 inside the United States, except that to Hawaii and Alaska they are \$10. International shipping costs are also \$10.

•Three Branches:



### Don't Connect Branches!

Shipping costs are \$5 inside the United States, except that to Hawaii and Alaska they are \$10. International shipping costs are also \$10.

#### Do not do this!



## Shipping Cost Flowchart

Shipping costs are \$5 inside the United States, except that to Hawaii and Alaska they are \$10. International shipping costs are also \$10.

Completed



Draw a flowchart for a program that reads a value  $\mathtt{temp}$  and prints "Frozen" if it is less than zero.

#### Answer:



What is wrong with the flowchart at right?

**Answer:** The "True" arrow from the first decision points into the "True" branch of the second decision, creating spaghetti code.



How do you fix the flowchart of Self Check 23?

**Answer:** Here is one solution. In Section 3.7, you will see how you can combine the conditions for a more elegant solution.



Draw a flowchart for a program that reads a value x. If it is less than zero, print "Error". Otherwise, print its square root.

#### Answer:



Draw a flowchart for a program that reads a value temp. If it is less than zero, print "Ice". If it is greater than 100, print "Steam". Otherwise, print "Liquid".


# **Problem Solving: Test Cases**

•Aim for complete *coverage* of all decision points:

- •There are two possibilities for the marital status and two tax brackets for each status, yielding four test cases
- •Test a handful of *boundary* conditions, such as an income that is at the boundary between two tax brackets, and a zero income
- If you are responsible for error checking (which is discussed in Section 3.8), also test an invalid input, such as a negative income

# **Choosing Test Cases**

•Choose input values that:

- Test boundary cases and 0 values
- A boundary case is a value that is tested in the code
- Test each branch

Test Case		Expected Output	Comment
30,000	S	3,000	10% bracket
72,000	\$	13,200	3,200 + 25% of 40,000
50,000	т	5,000	10% bracket
04,000	m	16,400	6,400 + 25% of 40,000
32,000	т	3,200	boundary case
0		0	boundary case

Using Figure 1 on page 85 as a guide, follow the process described in Section 3.6 to design a set of test cases for the <code>ElevatorSimulation.java</code> program in Section 3.1.

#### Answer:

Test Case	Expected Output	Comment
12	12	Below 13th floor
14	13	Above 13th floor
13	?	The specification is not clear— See Section 3.8 for a version of this program with error handling

What is a boundary test case for the algorithm in How To 3.1 on page 95? What is the expected output?

**Answer:** A boundary test case is a price of \$128. A 16 percent discount should apply because the problem statement states that the larger discount applies if the price is *at least* \$128. Thus, the expected output is \$107.52.

Using Figure 3 on page 99 as a guide, follow the process described in Section 3.6 to design a set of test cases for the EarthquakeStrength.java program in Section 3.3.

#### Answer:

Test	Expected	
Case	Output	Comment
9	Most structures fall	
7.5	Many buildings destroyed	
6.5	Many buildings	
5	Damage to poorly	
3	No destruction	
8.0	Most structures fall	Boundary case. In this program, boundary cases are not as significant because the behavior of an earthquake changes gradually.
-1		The specification is not clear—see Self Check 16 for a version of this program with error handling.

Suppose you are designing a part of a program for a medical robot that has a sensor returning an *x*- and *y*-location (measured in cm). You need to check whether the sensor location is inside the circle, outside the circle, or on the boundary (specifically, having a distance of less than 1 mm from the boundary). Assume the circle has center (0, 0) and a radius of 2 cm. Give a set of test cases.

#### Answer:

Test Case	Expected Output	Comment
(0.5, 0.5)	inside	
(4, 2)	outside	
(0, 2)	on the boundary	Exactly on the boundary
(1.414, 1.414)	on the boundary	Close to the boundary
(0, 1.9)	inside	Not less than 1 mm from the boundary
(0, 2.1)	outside	Not less than 1 mm from the boundary

## **Boolean Variables**

Boolean Variables

•A Boolean variable is often called a flag because it can be either up (true) or down (false)

boolean is a Java data type

•boolean failed = true;

•Can be either true or false

■Boolean Operators: & & and | |

- They combine multiple conditions
- ■& & is the *and* operator
- | | is the *or* operator



#### **Character Testing Methods**

The Character class has a number of handy methods that return a boolean value:

if (Character.isDi			
{  } Metho		Character Testing Methods	
		od	Examples of Accepted Characters
	isDig	it	0, 1, 2
	isLett	er	A, B, C, a, b, c
	isUpperCase		A, B, C
isLower isWhite		Case	a, b, c
		pace	space, newline, tab

## Combined Conditions: &&

Combining two conditions is often used in range checking
Is a value between two other values?
Both sides of the *and* must be true for the result to be true

if (temp > 0 && temp < 100)	А	В	A && B
<pre>{    System.out.println("Liquid"); }</pre>	true	true	true
	true	false	false
	false	true	false
	false	false	false

# Combined Conditions:

If only one of two conditions need to be trueUse a compound conditional with an or:

```
if (balance > 100 || credit > 100)
{
   System.out.println("Accepted");
}
```

If either is true

The result is true

А	В	A    B
true	true	true
true	false	true
false	true	true
false	false	false

## The not Operator: !

-If you need to invert a boolean variable or comparison, precede it with !

```
if (!attending || grade < 60)
{
   System.out.println("Drop?");
}
if (!attending || grade < 60)
{
   System.out.println("Drop?");
}</pre>
```

А	!A
true	false
false	true

•If using !, try to use simpler logic:

if (attending && (grade >= 60))

# and Flowchart

This is often called 'range checking'
 I sed to validate that input is between two





# or Flowchart

# Another form of 'range checking'Checks if value is outside a range



# **Boolean Operator Examples**

Table 5 Boolean Operator Examples				
	Expression	Value	Comment	
	0 < 200 && 200 < 100	false	Only the first condition is true.	
	0 < 200    200 < 100	true	The first condition is true.	
	0 < 200    100 < 200	true	The    is not a test for "either-or". If both conditions are true, the result is true.	
	0 < x && x < 100    x == -1	(0 < x && x < 100)    x == -1	The && operator has a higher precedence than the    operator (see Appendix B).	
0	0 < x < 100	Error	<b>Error:</b> This expression does not test whether x is between 0 and 100. The expression 0 < x is a Boolean value. You cannot compare a Boolean value with the integer 100.	
0	x && y > 0	Error	<b>Error:</b> This expression does not test whether x and y are positive. The left-hand side of && is an integer, x, and the right-hand side, $y > 0$ , is a Boolean value. You cannot use && with an integer argument.	
	! (0 < 200)	false	0 < 200 is true, therefore its negation is false.	
	frozen == true	frozen	There is no need to compare a Boolean variable with true.	
	frozen == false	!frozen	It is clearer to use ! than to compare with false.	

Suppose x and y are two integers. How do you test whether both of them are zero?

Answer: x == 0 & & y == 0

How do you test whether at least one of them is zero?

**Answer:** x == 0 | | y == 0

How do you test whether exactly one of them is zero?

**Answer:** (x == 0 & & y != 0) || (y == 0 & & x != 0)

What is the value of !!frozen?

Answer: The same as the value of frozen.

What is the advantage of using the type boolean rather than strings "false"/"true" or integers 0/1?

**Answer:** You are guaranteed that there are no other values. With strings or integers, you would need to check that no values such as "maybe" or -1 enter your calculations.

# **Common Error**

Combining Multiple Relational Operators

if (0 <= temp <= 100) // Syntax error!</pre>

•This format is used in math, but not in Java!

It requires two comparisons:

if (0 <= temp && temp <= 100)

This is also not allowed in Java:

if (input == 1 || 2) // Syntax error!

This also requires two comparisons:

if (input == 1 || input == 2)

# **Common Error**

#### -Confusing && and || Conditions

- -It is a surprisingly common error to confuse  ${}_{\&\,\&}$  and || conditions
- •A value lies between 0 and 100 if it is at least 0 *and* at most 100
- It lies outside that range if it is less than 0 or greater than 100
- •There is no golden rule; you just have to think carefully

# Short-Circuit Evaluation: &&

•Combined conditions are evaluated from left to right

•If the left half of an and condition is false, why look further?



# Short-Circuit Evaluation:

- •If the left half of the or is true, why look further?
- Java doesn't!
- Don't do these second:

#### Assignment

Output

```
if (temp <= 0 || temp >= 100)
{
   System.out.println("Not Liquid");
}
```



## De Morgan's Law



•To simplify conditions with negations of *and* or *or* expressions, it is usually a good idea to apply De Morgan's Law to move the negations to the innermost level.

# Input Validation

```
    Accepting user input is dangerous
```

- •Consider the Elevator program:
- •The user may input an invalid character or value

```
•Must be an integer
    •Scanner can help!
    •hasNextInt
    •True if integer
    •False if not
    •Then range check value
•We expect a floor number to be between 1 and 20
if (in.hasNextInt())
{
    int floor = in.nextInt();
    // Process the input value
    if
    (in.hasNextInt())
    {
        int floor = in.nextInt();
        // Process the input value
    }
    else
    {
        System.out.println("Not integer.");
    }
```

```
•NOT 0, 13 or > 20
```

## ElevatorSimulation2.java

```
public class ElevatorSimulation2
 7
 8
 9
       public static void main(String[] args)
10
        {
11
           Scanner in = new Scanner(System.in);
12
           System.out.print("Floor: ");
                                                           Input value validity checking
13
           if (!in.hasNextInt())
14
           £
15
              // Now we know that the user entered an integer
16
17
              int floor = in.nextInt();
18
19
              if (floor == 13)
20
              £
21
                 System.out.println("Error: There is no thirteenth floor.");
22
              }
23
                                                          Input value range checking
              else if (floor \leq 0 || floor > 20)
24
              £
25
                 System.out.println("Error: The floor must be between 1 and 20.");
26
              }
27
              else
28
              ş
                 // Now we know that the input is valid
29
```

## ElevatorSimulation2.java

```
30
31
                 int actualFloor = floor;
                 if (floor > 13)
32
33
                 £
34
                     actualFloor = floor - 1;
35
                 }
36
37
                 System.out.println("The elevator will travel to the actual floor "
38
                    + actualFloor);
39
              }
40
           }
41
           else
42
           £
43
              System.out.println("Error: Not an integer.");
44
           }
45
        }
46
    }
```

#### **Program Run**

Floor: 13 Error: There is no thirteenth floor.

In the ElevatorSimulation2 program, what is the output when the input is

- **a.** 100?
- **b.** –1?
- **c.** 20?
- d. thirteen?

#### Answer:

```
(a) Error: The floor must be between 1 and 20.
(b) Error: The floor must be between 1 and 20.
(c) 19
(d) Error: Not an integer.
```

Your task is to rewrite lines 19–26 of the ElevatorSimulation2 program so that there is a single if statement with a complex condition. What is the condition?

```
if (. . .)
{
   System.out.println("Error: Invalid floor number");
}
```

```
Answer: floor == 13 || floor <= 0 || floor > 20
```

In the Sherlock Holmes story "The Adventure of the Sussex Vampire", the inimitable detective uttered these words: "Matilda Briggs was not the name of a young woman, Watson, ... It was a ship which is associated with the giant rat of Sumatra, a story for which the world is not yet prepared." Over a hundred years later, researchers found giant rats in Western New Guinea, another part of Indonesia.

Suppose you are charged with writing a program that processes rat weights. It contains the statements

```
System.out.print("Enter weight in kg: ");
double weight = in.nextDouble();
What input checks should you supply?
```

**Answer:** Check for in.hasNextDouble(), to make sure a researcher didn't supply an input such as oh my. Check for weight <= 0, because any rat must surely have a positive weight. We don't know how giant a rat could be, but the New Guinea rats weighed no more than 2 kg. A regular house rat (*rattus rattus*) weighs up to 0.2 kg, so we'll say that any weight > 10 kg was surely an input error, perhaps confusing grams and kilograms. Thus, the checks are

```
if (in.hasNextDouble())
{
   double weight = in.nextDouble();
   if (weight <= 0)
   {
      System.out.println(
         "Error: Weight must be positive.");
   else if (weight > 10)
      System.out.println( "Error: Weight > 10 kg.");
   else
      Process valid weight.
else
   System.out.print("Error: Not a number");
```

Run the following test program and supply inputs 2 and three at the prompts. What happens? Why?

```
import java.util.Scanner
public class Test
{
    public static void main(String[] args)
    {
        Scanner in = new Scanner(System.in);
        System.out.print("Enter an integer: ");
        int m = in.nextInt();
        System.out.print("Enter another integer: ");
        int n = in.nextInt();
        System.out.println(m + " " + n);
    }
}
```

**Answer:** The second input fails, and the program terminates without printing anything.